#####

<schweikh@FreeBSD.org>
#######: 43126

######### ##### © 2002,2003,2004,2008 #### ############

####### ### ################## ######## ##### ####### ##########.

#####, #######, ####### ###### # ########## ### ### ######–############ ######## ##### ### ######## ##### ##### ####### ############ # ########### ###### #/### ###### #######.

###########, ############ ############### # ###–####### ### ########### ##### #########, ########## # ##–###### ######## #####. ##### ##### ########### ########## # #### #########, # ####### ####### ######## # ######## #####, # ########### ########### #### ### ### ###.

2013#11#07 #####.

#########

#######: ######### ################## ######### ####–############ ## ######## ####### ####### #######, ####### ########## #### ##### ####### ###### # ############# # ####–######## # ###### ############### # ########### #######. #### ## #########, ### ######### make world ######## ########## ###–#####, ## ####### #### ####### ######### ### ####### ## make evenmore.

##########

1. ######## 2
2. ###### ### (##) ##### ####### #### #######? 2
3. ############### ########## 4
4. #### ######: ######### ####### 4
5. #### ######: ######### ###### 10
6. #### ###### 15
7. ########### 15
8. ##### 16

1.

make world? ########## #### ###–#####, ########### ### ####### ##### #### ##### ####### ## #####. #### #######–### #### installworld ########### ## ########, # ### ######## ################# ##–#####, ####### ##### #### ## ###########. #### #### installworld ############ ###–######, # ##### #### ## ###########. ##### ######### ###### ### ###### ##### ## # ######### #####, ####### ## ###### ####### #####.

#######. ######## ######, # #### ########, ############ ### ##, ### ##### ## ######## ####### ##–#### #######, ##, # ### ## ######### ####### ##### ######## ##########. ###### ####### ######## ########, ### ### ##### ################/############## ### #### ##### # #######, # ##### ######### ### ###### ######### #########. #### ## #######, ### ### ###### #### ###### #### ################, ## ####### ######.

2. ###### ### (##) ##### ####### #### #######?

######. # ### ####### ####### ########## # ###### ######### ###### ########## #### # ################ ##########.

######## # ######## ########## ########### # ###, ### ### ######### ########## # ###, ###, #### # ### ##### ##############.

- ###### ### ############ ### ######### ### ################# ############### ####### # ######## # ########## ######## (##, ###, ###). ### ## ##### #######–###### ######### ########## make buildworld.
- ### ## ##### ############## ###### ####### # ######### ####### ### ########## #######.
- ### ## ##### ######### ######### # ####### ##### ### ###.
- ### ## ##### ####### #####, # #### ############## ### ################# ####–###.
- ######## ######## ### ########## ############## ######## ##### ######### ##–########.
- # #########, ## ##### ## ##### ###### ########, ######## ############### ###–######## ########## ######### ##########.

#######, ######### # ###########, ## ######### ######## ############ #######. ### #### ########### ###### ###### # ####. ######### ######## #####, ##### ########## ####### # ###–###### ###### ###### ################; ### ######## ##### ######## # ##### ###–

######### ########. #### ## ########## ####### ########## ########## ######–##, ###### ###### # #### ########## ####### ####### # ######## #########.

####### #### ####### ###### ### ### ########. ## ######### ######: ########–##### ########## ####### ### ######### ##### # ###### ###### #########, ### #### ##### ####### ########## # ############### ##### ##### ######. ###–### ################ ##### ##### #### ########## # ############### #####, # ##########(8) ###### ############ # ###, ### ########## ## #######. ###### ##–####### ##### ####### ##### #### ######### # ######, ###### ## #######, ##### ## ####### ######### ###### # ##### #######. ######## #######, ## ######## ##### ### #####, ### #### ###### ### ############ ##### #### ###### #######, #### ##### ####### make:

1. stage_1.sh: ######## ##### ########## ####### # ###### ######## # ########## #### ########## ########## ######## ########## ########## ######. ##### ######## ##### #######.

2. stage_2.sh: ######### ######### ######.

3. stage_3.mk: ########## ########## ######### ########### ###########, ####–########## ## ########## #####.

####, ### ## ############## ####### #### ####### ### ########## ###### ####### # # ####### ########## ###### #########, ### ### ######## ##########–######, ###### ##### ############ ## ######## ### ############## ######## ##–#####. # ##### #######, ### ###### ## ############ ############## ##########, ## ###### ######## ########, ######## ###### ####### # ######### ##############.

####, ## ####### # #### ######### ############ ####### ##### #### #######, ### ### ### #########. ### ##### ##########, ### ######### # ########## ####### # #### ## ###### ###### ### ###### ########## #######. ### ###### #### ## ####–##### #### ####### ########## ####### (#####, ### ####, ##########, ##########, ######### #########, #### ###### ############ ######### # ### #####) # ####–### ######### ####### ##########. ######## #### ####### ## ########## ## ###### ###### ############. #### ##### ######## ########## ################## # ###–### #########, # ## ######## #### ######## ############ ####### ##########–### #######. # ######, #### ## ###### ####### ####### ## ###### ######, ####### # ######### /usr/src/Makefile # ######## #########, ######## ######### make buildworld.

#######, ####### ########## # ####### #### #######, ####### #### ##########–### #######, ####### ## ###### ##### # ####.

- ### ########## ###### ## ###### ##### ####### ###### ############ # ####### ######. #### ## ###### #### # ########, ########## # ###### ############ ###–#########, ## ###### #### ###### # #######, # ######## ######## ########## ####### #####. #####, ############ ### ###### stage_2.conf.default ####, ######### ### ###### ##### 8 ##### ## ########### ######## (4 ## ######## ###### ##########

##########.###). #### ## ############ ############ ######, # ## #####, ## ## ###### ########## ######### ##### #######, ######## ## 10 #####.

3. ###############

####, ##### ############### ######## ####### #### #######, ### ##### #####:

- ########## ####### ####### # ######### ######## # ####### ######.
- ## ####### #### #### ############### ######, #### ##### ############### ##### #######.
- #### ###### # ###########(8). ### ## ####### #### ########## ###### ### ##–##########.
- #### # ### ### ########### ### ###### ##### # ########: ############### ##### ### ##### ####### ######.
- ###### ##### ######### ######## ## ##### ########## ########## ######, ##(1).
- #######, ## ###### ##### ######### ########## ####### ## ######## ##### ##–#####, #### ############, #### ## ################# #####.

4. #### ######: #########

######, # ####### ### ######### ########### ### ###############. ##### ####, ### ####–######## ######### #### #########, # ##### ######### ### # ###### ## ###### ########. ### ######### ######### ###### ###### ################ ###### ### ######### ######### ###### ### ######## ######### # ####### # #####.

stage_1.sh, # ## ########### # ####–######## ##########,

```
# ./stage_1.sh default
```

stage_1.conf.default # ########## ######## # #### stage_1.log.default.

stage_1.conf.default. ### ########## ########## ### # ###–###### ###### ### ####, ##### ## ############## ##### ############## ## ####–###### ########. # ######### ######## ################ ## #####, ####### ## ###### ##########. ################ ###### ###### ############ ###### ####–### ### ########, create_file_systems, create_etc_fstab, copy_files # all_remaining_customization (# ###–###, #### ### ##### #####: ###### # ##### ################## ### ##### ########–## ## stage_1.sh).

####### ########## ######### # ######### ########:

- ######### ########.

  # ## ####### ########## ####### ###### ######## ####### ### #### #######. ### #######, ### #######, ##### ## ####### #### ## ###### ####### ### /, /usr # /var # ######### /tmp, ############ ############# ####### # /var/tmp. ######## # ######### ######## ####### # ###### ########## ####### # /home (######## ##–###### #############), /home/ncvs (##### ############# #######), /usr/ports (####–## ######), /src (######### ########## ## ######### ####### ######## #######) # /share (######### ######### ############ ######, ######### ##### ####### ## #####, ########, #### ####### ###############).

- ##### ##########.

  ### ##, ### ## ###### ##### ##### ##### ######## ##### ####### # #### ## ##–##### ####### #####. ####### ###### ## ######## # ######## # ################ ##### ####### ## ##### ####### ##### # ####### ######### #### #### ####### ###### ########## # ###, ### ############ # ########## ########## ######## ######### ######## # ##########: ## ###### ##### ######## #### ###### ####, ###### # ################ ########## ##### ######## ##### ######## # ##### ##########. #### ##### ######### ########## ##### ######### #####, ## ### ##–### ########## SIGSYS, ####### ########## ######, ### ### ###### #### ## ########### #### ##### #####. # ######## # ###### ######## ### ####### ########## ##### ####/####5.8.

###, ### ######### stage_1.sh, #########, ### ## ######### ####### ######## ### ########## # make installworld installkernel, ####:

- ############### ################ #### ###### ####

- ####### ######### make buildworld

- ####### ######### make buildkernel KERNCONF=whatever

stage_1.sh ###### ###, # ################ ####, ############# # ########## ####### # #####, ######## ########## ## ######### # ###, ### ####–##### # ######## /usr/src, mergemaster ##### ########## ### ## ######### #### #####–###. # ########## ########## #########. #### ### ####### ######## ## #######, ## ###### ###### ######## ######## ##### # ##### ########## ####### (#### ###### ### ### ########. ###### #####, ### ## ##### ### ######, #### #### ## ##### ###### ######## ### ########### -STABLE, # ###### # -CURRENT. ######### ##### ######### ##############). ########### ###### ####### mergemaster #########, ### ########–########## ###### ############# ###, ### ######### # /usr/src, # ######### ####.

stage_1.sh ########### ## ###### #######, ####### ########## ######## (###–###### ######### ### ##########) ##### set -e, ### ### ## ## ########## ######.

###########, #### ## ########### ############### ########## ######–###, ### #######, ##### ########. ## ###### ######### ### ###### # ##### ###### stage_1.conf.default ##### ###, ### ########## ######.

stage_1.sh ## ######## mergemaster. #### #### ####### ###### ########### ## #########, ## ####### ######### # # ##### #######

```
*** Comparison complete
*** Saving mtree database for future upgrades

Do you wish to delete what is left of -/var/tmp/temproot.stage1? [no] no
```

##########, ######## no ### ###### ####### #####. ####### # ###, ### mergemaster ####### ######### ###### ####### ##### # ######## /var/tmp/temproot.stage1, ####### ##### ##### ########### # ##### ####### (# ######, #### ## ### ### ###).

mergemaster ########## ############# ## ##### # #######, ##### ## ##–########## ##### login.conf:

```
*** You chose the automatic install option for files that did not
    exist on your system.  The following were installed for you:
      -/newroot/etc/defaults/rc.conf
      -...
      -/newroot/COPYRIGHT

*** You installed a new aliases file into -/newroot/etc/mail, but
    the newaliases command is limited to the directories configured
    in sendmail.cf.  Make sure to create your aliases database by
    hand when your sendmail configuration is done.

*** You installed a login.conf file, so make sure that you run
    -'/usr/bin/cap_mkdb -/newroot/etc/login.conf'
     to rebuild your login.conf database

    Would you like to run it now? y or n [n]
```

########, ### ### stage_1.sh ##### ######### ###_####(1) # ##### ###–###.

stage_1.conf.default, ####### ## ###### ##### ########## ######–########. # ############ ###### ######### ########## # ###, ### ########## ##–######.

```
# This file: stage_1.conf.default, sourced by stage_1.sh.
#
# $Id: stage_1.conf.default,v 1.5 2011-05-14 20:44:31 hrs Exp $
# $FreeBSD: head/en_US.ISO8859-1/articles/fbsd-from-scratch/stage_1.conf.default 38826 -
2012-05-17 19:12:14Z hrs $

# Root mount point where you create the new system. Because it is only
# used as a mount point, no space will be used on that file system as all
```

```
# files are of course written to the mounted file system(s).
DESTDIR="/newroot"

# Where your src tree is.
SRC="/usr/src"

# Where your obj is.
MAKEOBJDIRPREFIX="/usr/obj"

# Your kernel config name as from make buildkernel KERNCONF=...
KERNCONF="HAL9000"

# Your target architecture as used for make buildworld TARGET=...
# If you did not specify a TARGET when building world, it defaulted
# to the build architecture (run -"uname --m" to find out if you are unsure).
TARGET="i386"  # amd64 arm i386 ia64 mips pc98 powerpc sparc64

# Available time zones are those under -/usr/share/zoneinfo.
TIMEZONE="Europe/Berlin"



#
# The create_file_systems function must create the mountpoints under
# DESTDIR, create the file systems, and then mount them under DESTDIR.
#
create_file_systems () {
  # The new root file system. Mandatory.
  # Change DEVICE names.
  DEVICE=/dev/daXYZs1a
  mkdir --m 755 --p ${DESTDIR}
  chown root:wheel ${DESTDIR}
  newfs --U ${DEVICE}
  mount --o noatime ${DEVICE} ${DESTDIR}

  # Additional file systems and initial mount points. Optional.
  DEVICE=/dev/daXYZs1e
  mkdir --m 755 --p ${DESTDIR}/var
  chown root:wheel ${DESTDIR}/var
  newfs --U ${DEVICE}
  mount --o noatime ${DEVICE} ${DESTDIR}/var

  DEVICE=/dev/daXYZs1e
  mkdir --m 755 --p ${DESTDIR}/usr
  chown root:wheel ${DESTDIR}/usr
  newfs --U ${DEVICE}
  mount --o noatime ${DEVICE} ${DESTDIR}/usr
}

#
# The create_etc_fstab function must create an fstab matching the
# file systems created in create_file_systems.
#
create_etc_fstab () {
```

```
  cat <<EOF >${DESTDIR}/etc/fstab
# Device        Mountpoint          FStype    Options             Dump Pass#
/dev/da0s1b      none                swap      sw                  0    0
/dev/da1s1b      none                swap      sw                  0    0
/dev/da2s2b      none                swap      sw                  0    0
/dev/da3s2b      none                swap      sw                  0    0
/dev/da0s1a      -/                  ufs       rw,noatime          1    1
/dev/da0s1e      -/var               ufs       rw,noatime          1    1
/dev/da2s1e      -/usr               ufs       rw,noatime          1    1
/dev/vinum/Share -/share             ufs       rw,noatime          0    2
/dev/vinum/home  -/home              ufs       rw,noatime          0    2
/dev/vinum/ncvs  -/home/ncvs         ufs       rw,noatime          0    2
/dev/vinum/ports -/usr/ports         ufs       rw,noatime          0    2
/dev/ad1s1a      -/flash             ufs       rw,noatime          0    0
/dev/ad0s1       -/2k                ntfs      ro,noauto           0    0
/dev/ad0s6       -/linux             ext2fs    ro,noauto           0    0
#
/dev/cd0         -/cdrom             cd9660    ro,noauto           0    0
/dev/cd1         -/dvd               cd9660    ro,noauto           0    0
proc             -/proc              procfs    rw                  0    0
linproc          -/compat/linux/proc  linprocfs rw                 0    0
EOF
  chmod 644 ${DESTDIR}/etc/fstab
  chown root:wheel ${DESTDIR}/etc/fstab
}

#
# The copy_files function is used to copy files before mergemaster is run.
#
copy_files () {
  # Add or remove from this list at your discretion. Mostly mandatory.
  for f in \
    -/.profile \
    -/etc/devd.conf \
    -/etc/devd.rules \
    -/etc/exports \
    -/etc/group \
    -/etc/hosts \
    -/etc/inetd.conf \
    -/etc/ipfw.conf \
    -/etc/make.conf \
    -/etc/master.passwd \
    -/etc/nsswitch.conf \
    -/etc/ntp.conf \
    -/etc/printcap \
    -/etc/profile \
    -/etc/rc.conf \
    -/etc/resolv.conf \
    -/etc/src.conf \
    -/etc/sysctl.conf \
    -/etc/ttys \
    -/etc/mail/aliases \
    -/etc/mail/aliases.db \
```

```
    -/etc/mail/hal9000.mc \
    -/etc/mail/service.switch \
    -/etc/ssh/*key* \
    -/etc/ssh/*_config \
    -/etc/X11/xorg.conf \
    -/var/cron/tabs/* \
    -/root/.profile \
    -/boot/*.bmp \
    -/boot/loader.conf \
    -/boot/device.hints -; do
    cp --p ${f} ${DESTDIR}${f}
  done
}

#
# Everything else you want to tune in the new system.
# NOTE: Do not install too many binaries here. With the old system running and
# the new binaries and headers installed you are likely to run into bootstrap
# problems. Ports should be compiled after you have booted in the new system.
#
all_remaining_customization () {
  # Without the compat symlink the linux_base files end up on the root fs:
  cd ${DESTDIR}
  mkdir --m 755 usr/compat; chown root:wheel usr/compat; ln --s usr/compat
  mkdir --m 755 usr/compat/linux;      chown root:wheel usr/compat/linux
  mkdir --m 555 usr/compat/linux/proc; chown root:wheel usr/compat/linux/proc
  mkdir --m 755 boot/grub;             chown root:wheel boot/grub
  mkdir --m 755 linux 2k;              chown root:wheel linux 2k
  mkdir --m 755 src;                   chown root:wheel src
  mkdir --m 755 share;                 chown root:wheel share
  mkdir --m 755 dvd cdrom flash;       chown root:wheel dvd cdrom flash
  mkdir --m 755 home;                  chown root:wheel home
  mkdir --m 755 usr/ports;             chown root:wheel usr/ports

  # Create the ntp and slip log files.
  touch ${DESTDIR}/var/log/ntp ${DESTDIR}/var/log/slip.log

  # Make -/usr/src point to the right directory. Optional.
  # Note: some ports need part of the src tree, e.g. emulators/kqemu,
  # sysutils/lsof, sysutils/fusefs, -...
  cd ${DESTDIR}/usr
  if test -"${SRC}" -!= -/usr/src; then
    rmdir src; ln --s ${SRC}
  fi
  if test -"${MAKEOBJDIRPREFIX}" -!= -/usr/obj; then
    rmdir obj; ln --s ${MAKEOBJDIRPREFIX}
  fi

  # My personal preference is to symlink tmp --> var/tmp. Optional.
  cd ${DESTDIR}; rmdir tmp; ln --s var/tmp

  # Make spooldirs for the printers in my -/etc/printcap.
  cd ${DESTDIR}/var/spool/output/lpd; mkdir --p as od ev te lp da
```

```
  touch ${DESTDIR}/var/log/lpd-errs

  # If you do not have -/home on a shared partition, you may want to copy it:
  # mkdir --p ${DESTDIR}/home
  # cd -/home; tar cf -- -. -| (cd ${DESTDIR}/home; tar xpvf --)
}

# vim: tabstop=2:expandtab:shiftwidth=2:syntax=sh:
# EOF $RCSfile: stage_1.conf.default,v $
```

######## stage_1.conf.default.

#######, ######## ### ######## ###########:

- ############## ###### ############# # #####.
- ########### # ######## ## ######## # ############## ########### ######.
- ########## ######### #### # ###.
- ###### ##### ###### ################ #########, ########, /etc/ttys # inetd.

#########, ## ## ##### ########, #### ## ##### ######## ###### ####. ########, ## ########### ##### ### ######### ###### # #11. ###### ### ######, ###### #####, ########## ##########, ############## # ######## ###–###### ########, ########, ##### ### ##########®. #11 ## ##### ########, #### ## ## ############# ######, ########## # #########.

5. #### ######: #########

##########

(### ################) ########. # #### ###### stage_2.sh ##### ############ ##### ## #####, ### ######## ##–#### pkg_add. # ########, ### ## ######## ######## ##### ######. ##### ## ############## ## ##### ###### # ############ ###–#### # ############## ######.

######### ###### stage_2.sh ##########, ### # ############ ### ######## #####. ## ##### #### ######## ##### ########## ### # ##### ########## ### #####, ######## ### ###########. ## ############ *dryrun*######### (-n) ### ###### ####, ### #####

#########. ## ########## ### ##### #####, ### stage_1.sh, # ###### ##### ##########, ########### ## ################ ####, # #######

```
# ./stage_2.sh default
```

####### ##### ######### ######## ###### ## stage_2.conf.default.

####, #####–###### #########: ######### # ####, ## ######## ########### ####### ####### #########, ####### ##### ############ # ############# #### (## #########: make install BATCH=yes < /dev/null). ###### ###### # ######, ############ # ####### #, ####–########. # ########### ####### # ### ########### ###### ######## ######### # ####. ###### ######### ##### ##### #### ##### ######### ### ###### ######## make##########, # #######:

```
www mozilla make WITHOUT_MAILNEWS=yes WITHOUT_CHATZILLA=yes install
```

#########–#### ######## ######## make:

```
java jdk16           echo true > files/license.sh; make install BATCH=yes < -/dev/null
print acroread8      yes accept -| make install PAGER=ls
x11-fonts gnu-unifont make install && mkfontdir -/usr/local/lib/X11/fonts/local
news inn-stable      CONFIGURE_ARGS="--enable-uucp-rnews ---enable-setgid-inews" make install
```

#################, ### ######## # #######, ######## ########## ### ####### ########## ########. ########, ### ###### ### ####/ ########## ######## ######## ############# ####### ########## ########## CONFIGURE_ARGS. #### Makefile ##### ##### ############ ### ### ######### #####–### # ######### ######### ###### ########## #########. ######## # ######## ##### ########## # ######### ###### ##

```
news inn-stable make CONFIGURE_ARGS="--enable-uucp-rnews ---enable-setgid-inews" install
```

########### # ###, ### # ######### ###### ######## ##### #############, ## ## #########. ##### ####### ###### ####### ## ########### #####.

######### # ###, ### #### ##### ## ########## ############# ##### #########, ## #### ## ###### ######## ###### ## ############ ########## ##### ###### ##### ####, ### ## ## ####### ## ####. #### ### ### ## ##########, ## ### ##### ######### ########### ###### ## ###### ####### ######, ############ # #### #########, # ##### ######## ###########. #### ###### stage_2.sh ########## ######### #### ### ######### ######, ######## ##### #### # ####.

stage_2.conf.default. ### ####### ############## ## ##### ######### #### ######### LOGDIR/category+port.

```
# This file: stage_1.conf.default, sourced by stage_1.sh.
#
```

```
# $Id: stage_1.conf.default,v 1.5 2011-05-14 20:44:31 hrs Exp $
# $FreeBSD: head/en_US.ISO8859-1/articles/fbsd-from-scratch/stage_1.conf.default 38826 -
2012-05-17 19:12:14Z hrs $

# Root mount point where you create the new system. Because it is only
# used as a mount point, no space will be used on that file system as all
# files are of course written to the mounted file system(s).
DESTDIR="/newroot"

# Where your src tree is.
SRC="/usr/src"

# Where your obj is.
MAKEOBJDIRPREFIX="/usr/obj"

# Your kernel config name as from make buildkernel KERNCONF=...
KERNCONF="HAL9000"

# Your target architecture as used for make buildworld TARGET=...
# If you did not specify a TARGET when building world, it defaulted
# to the build architecture (run -"uname --m" to find out if you are unsure).
TARGET="i386"  # amd64 arm i386 ia64 mips pc98 powerpc sparc64

# Available time zones are those under -/usr/share/zoneinfo.
TIMEZONE="Europe/Berlin"


#
# The create_file_systems function must create the mountpoints under
# DESTDIR, create the file systems, and then mount them under DESTDIR.
#
create_file_systems () {
  # The new root file system. Mandatory.
  # Change DEVICE names.
  DEVICE=/dev/daXYZs1a
  mkdir --m 755 --p ${DESTDIR}
  chown root:wheel ${DESTDIR}
  newfs --U ${DEVICE}
  mount --o noatime ${DEVICE} ${DESTDIR}

  # Additional file systems and initial mount points. Optional.
  DEVICE=/dev/daXYZs1e
  mkdir --m 755 --p ${DESTDIR}/var
  chown root:wheel ${DESTDIR}/var
  newfs --U ${DEVICE}
  mount --o noatime ${DEVICE} ${DESTDIR}/var

  DEVICE=/dev/daXYZs1e
  mkdir --m 755 --p ${DESTDIR}/usr
  chown root:wheel ${DESTDIR}/usr
  newfs --U ${DEVICE}
  mount --o noatime ${DEVICE} ${DESTDIR}/usr
}
```

```
#
# The create_etc_fstab function must create an fstab matching the
# file systems created in create_file_systems.
#
create_etc_fstab () {
  cat <<EOF >${DESTDIR}/etc/fstab
# Device        Mountpoint          FStype    Options             Dump Pass#
/dev/da0s1b     none                swap      sw                  0    0
/dev/da1s1b     none                swap      sw                  0    0
/dev/da2s2b     none                swap      sw                  0    0
/dev/da3s2b     none                swap      sw                  0    0
/dev/da0s1a     -/                  ufs       rw,noatime          1    1
/dev/da0s1e     -/var               ufs       rw,noatime          1    1
/dev/da2s1e     -/usr               ufs       rw,noatime          1    1
/dev/vinum/Share -/share            ufs       rw,noatime          0    2
/dev/vinum/home  -/home             ufs       rw,noatime          0    2
/dev/vinum/ncvs  -/home/ncvs        ufs       rw,noatime          0    2
/dev/vinum/ports -/usr/ports        ufs       rw,noatime          0    2
/dev/ad1s1a     -/flash             ufs       rw,noatime          0    0
/dev/ad0s1      -/2k                ntfs      ro,noauto           0    0
/dev/ad0s6      -/linux             ext2fs    ro,noauto           0    0
#
/dev/cd0        -/cdrom             cd9660    ro,noauto           0    0
/dev/cd1        -/dvd               cd9660    ro,noauto           0    0
proc            -/proc              procfs    rw                  0    0
linproc         -/compat/linux/proc  linprocfs rw                 0    0
EOF
  chmod 644 ${DESTDIR}/etc/fstab
  chown root:wheel ${DESTDIR}/etc/fstab
}

#
# The copy_files function is used to copy files before mergemaster is run.
#
copy_files () {
  # Add or remove from this list at your discretion. Mostly mandatory.
  for f in \
    -/.profile \
    -/etc/devd.conf \
    -/etc/devd.rules \
    -/etc/exports \
    -/etc/group \
    -/etc/hosts \
    -/etc/inetd.conf \
    -/etc/ipfw.conf \
    -/etc/make.conf \
    -/etc/master.passwd \
    -/etc/nsswitch.conf \
    -/etc/ntp.conf \
    -/etc/printcap \
    -/etc/profile \
    -/etc/rc.conf \
```

```
    -/etc/resolv.conf \
    -/etc/src.conf \
    -/etc/sysctl.conf \
    -/etc/ttys \
    -/etc/mail/aliases \
    -/etc/mail/aliases.db \
    -/etc/mail/hal9000.mc \
    -/etc/mail/service.switch \
    -/etc/ssh/*key* \
    -/etc/ssh/*_config \
    -/etc/X11/xorg.conf \
    -/var/cron/tabs/* \
    -/root/.profile \
    -/boot/*.bmp \
    -/boot/loader.conf \
    -/boot/device.hints -; do
    cp --p ${f} ${DESTDIR}${f}
  done
}

#
# Everything else you want to tune in the new system.
# NOTE: Do not install too many binaries here. With the old system running and
# the new binaries and headers installed you are likely to run into bootstrap
# problems. Ports should be compiled after you have booted in the new system.
#
all_remaining_customization () {
  # Without the compat symlink the linux_base files end up on the root fs:
  cd ${DESTDIR}
  mkdir --m 755 usr/compat; chown root:wheel usr/compat; ln --s usr/compat
  mkdir --m 755 usr/compat/linux;      chown root:wheel usr/compat/linux
  mkdir --m 555 usr/compat/linux/proc; chown root:wheel usr/compat/linux/proc
  mkdir --m 755 boot/grub;             chown root:wheel boot/grub
  mkdir --m 755 linux 2k;              chown root:wheel linux 2k
  mkdir --m 755 src;                   chown root:wheel src
  mkdir --m 755 share;                 chown root:wheel share
  mkdir --m 755 dvd cdrom flash;       chown root:wheel dvd cdrom flash
  mkdir --m 755 home;                  chown root:wheel home
  mkdir --m 755 usr/ports;             chown root:wheel usr/ports

  # Create the ntp and slip log files.
  touch ${DESTDIR}/var/log/ntp ${DESTDIR}/var/log/slip.log

  # Make -/usr/src point to the right directory. Optional.
  # Note: some ports need part of the src tree, e.g. emulators/kqemu,
  # sysutils/lsof, sysutils/fusefs, -...
  cd ${DESTDIR}/usr
  if test -"${SRC}" -!= -/usr/src; then
    rmdir src; ln --s ${SRC}
  fi
  if test -"${MAKEOBJDIRPREFIX}" -!= -/usr/obj; then
    rmdir obj; ln --s ${MAKEOBJDIRPREFIX}
  fi
```

```
  # My personal preference is to symlink tmp --> var/tmp. Optional.
  cd ${DESTDIR}; rmdir tmp; ln --s var/tmp

  # Make spooldirs for the printers in my -/etc/printcap.
  cd ${DESTDIR}/var/spool/output/lpd; mkdir --p as od ev te lp da
  touch ${DESTDIR}/var/log/lpd-errs

  # If you do not have -/home on a shared partition, you may want to copy it:
  # mkdir --p ${DESTDIR}/home
  # cd -/home; tar cf -- -. -| (cd ${DESTDIR}/home; tar xpvf --)
}

# vim: tabstop=2:expandtab:shiftwidth=2:syntax=sh:
# EOF $RCSfile: stage_1.conf.default,v $
```

######## stage_2.conf.default.

6. ####

#####. ######### ## ### ####### ######### #########. ###### ### ##### # ############ ###### #### # #### ##–#######. # ### ## ############# ### ######### # ##### ####### stage_2.sh. ###### # #####, ### #### ############## ######## ##### ########## ##### # ############ ### ######### ############, # ### ####### ########## ####.

Makefile, ###### ### ### ######### ##### ######## ##, ### ## ###### ###############, ######### ####### #######:

```
# make –f stage_3.mk target
```

stage_2.sh, #########, ### #### stage_3.mk ##### ######## ##### ####### #### # #######, ######## ### ## ######### ############ ###### #### ########## ### ########## # ##### #######.

7.

################## ######### ##### ##### ######### ##########, #### ### ####–#### ############ # ## ############ ####### make BATCH=YES install. ### ########## ###### ############## ######## ## #####, ### #### yes # ##### ## ###### # #####–### ######### ############ ##########. #### ##### ##### ########## ## ####–######## ########## #####, ## ###### ########## ############## ###### ## #### ############ ####### (# #######: yes | make install). ### ######### ###### ### ######## ###########, ### ######### ######### ############ ####### # ############## ## ##########. #### #### ######### ####### ### #####/########8 ### ####/###16.

###–###. ###### ######, ## ## ######, ##### # ######## ## ###### ###### ### #######–### ################# #####. # #### /etc/group ##### #### ######### ##### ######, ### # /etc/passwd ##### ########## ############## ####. ### ### ### ########## # #######. ####### ########## ################# ##### ## ###### # ##### ####### ##### # ########## ####### ######### ##########, ## # #### ####### ### ## ###. #### ## ########## ####### ############ ######## (##### ############## ###–### ######), ## ###### ############ ####### mergemaster ### ###### # ##########, #### ## ###### ########## ########## #### ######### ######### # ########### ###### ##############. # #########, mergemaster ######## ###### # ####### ######## ######### #######, # ## # ###### #######, ################ #######. ######, ### ######### ########## ########## ########## ############## ### ####, ##### # ## ######, # ###### ################ ##### ## ### #### # #####. ### ########### ##### ####### #########, # ##### ##### ########## ################ ###### ### ##, ### # stage_3.mk # ######### ######### # ####### ###### make. ########, ### ###–############## ##### ######, httpd.conf, ##### ##### config_apache.

```
@if -! cmp --s -/usr/local/etc/apache2/httpd.conf httpd.conf; then \
   echo -"ATTENTION: the httpd.conf has changed. Please examine if"; \
   echo -"the modifications are still correct. Here is the diff:"; \
   diff --u -/usr/local/etc/apache2/httpd.conf httpd.conf; \
fi
```

cp /usr/local/etc/apache2/httpd.conf httpd.conf.

7-CURRENT ## 7-CURRENT # 8-CURRENT ## 8-CURRENT, ## #### # ####### ## ####### ########## 8-CURRENT ## ####### 7-STABLE # ########. ##### ########## ######–### ##### ######## # ####### ######## ######## # ######, ### #### ####### ##–### ######### ##### #######. ############# ####### #### ####### ### #######–### ###### ##### STABLE ###### ######### ############# (#### # ### ## ######## ##### ######).

8.

#####, ####### ### ##### ##### ### ################, ### ### ######## ####.

stage_1.sh, ####### ## ## ###### ##############.

```
# This file: stage_1.conf.default, sourced by stage_1.sh.
#
# $Id: stage_1.conf.default,v 1.5 2011-05-14 20:44:31 hrs Exp $
```

```
# $FreeBSD: head/en_US.ISO8859-1/articles/fbsd-from-scratch/stage_1.conf.default 38826 -
2012-05-17 19:12:14Z hrs $

# Root mount point where you create the new system. Because it is only
# used as a mount point, no space will be used on that file system as all
# files are of course written to the mounted file system(s).
DESTDIR="/newroot"

# Where your src tree is.
SRC="/usr/src"

# Where your obj is.
MAKEOBJDIRPREFIX="/usr/obj"

# Your kernel config name as from make buildkernel KERNCONF=...
KERNCONF="HAL9000"

# Your target architecture as used for make buildworld TARGET=...
# If you did not specify a TARGET when building world, it defaulted
# to the build architecture (run -"uname --m" to find out if you are unsure).
TARGET="i386"  # amd64 arm i386 ia64 mips pc98 powerpc sparc64

# Available time zones are those under -/usr/share/zoneinfo.
TIMEZONE="Europe/Berlin"


#
# The create_file_systems function must create the mountpoints under
# DESTDIR, create the file systems, and then mount them under DESTDIR.
#
create_file_systems () {
  # The new root file system. Mandatory.
  # Change DEVICE names.
  DEVICE=/dev/daXYZs1a
  mkdir --m 755 --p ${DESTDIR}
  chown root:wheel ${DESTDIR}
  newfs --U ${DEVICE}
  mount --o noatime ${DEVICE} ${DESTDIR}

  # Additional file systems and initial mount points. Optional.
  DEVICE=/dev/daXYZs1e
  mkdir --m 755 --p ${DESTDIR}/var
  chown root:wheel ${DESTDIR}/var
  newfs --U ${DEVICE}
  mount --o noatime ${DEVICE} ${DESTDIR}/var

  DEVICE=/dev/daXYZs1e
  mkdir --m 755 --p ${DESTDIR}/usr
  chown root:wheel ${DESTDIR}/usr
  newfs --U ${DEVICE}
  mount --o noatime ${DEVICE} ${DESTDIR}/usr
}
```

```
#
# The create_etc_fstab function must create an fstab matching the
# file systems created in create_file_systems.
#
create_etc_fstab () {
  cat <<EOF >${DESTDIR}/etc/fstab
# Device        Mountpoint          FStype    Options             Dump Pass#
/dev/da0s1b      none               swap      sw                  0    0
/dev/da1s1b      none               swap      sw                  0    0
/dev/da2s2b      none               swap      sw                  0    0
/dev/da3s2b      none               swap      sw                  0    0
/dev/da0s1a      -/                 ufs       rw,noatime          1    1
/dev/da0s1e      -/var              ufs       rw,noatime          1    1
/dev/da2s1e      -/usr              ufs       rw,noatime          1    1
/dev/vinum/Share -/share            ufs       rw,noatime          0    2
/dev/vinum/home  -/home             ufs       rw,noatime          0    2
/dev/vinum/ncvs  -/home/ncvs        ufs       rw,noatime          0    2
/dev/vinum/ports -/usr/ports        ufs       rw,noatime          0    2
/dev/ad1s1a      -/flash            ufs       rw,noatime          0    0
/dev/ad0s1       -/2k               ntfs      ro,noauto           0    0
/dev/ad0s6       -/linux            ext2fs    ro,noauto           0    0
#
/dev/cd0         -/cdrom            cd9660    ro,noauto           0    0
/dev/cd1         -/dvd              cd9660    ro,noauto           0    0
proc             -/proc             procfs    rw                  0    0
linproc          -/compat/linux/proc  linprocfs rw                0    0
EOF
  chmod 644 ${DESTDIR}/etc/fstab
  chown root:wheel ${DESTDIR}/etc/fstab
}

#
# The copy_files function is used to copy files before mergemaster is run.
#
copy_files () {
  # Add or remove from this list at your discretion. Mostly mandatory.
  for f in \
    -/.profile \
    -/etc/devd.conf \
    -/etc/devd.rules \
    -/etc/exports \
    -/etc/group \
    -/etc/hosts \
    -/etc/inetd.conf \
    -/etc/ipfw.conf \
    -/etc/make.conf \
    -/etc/master.passwd \
    -/etc/nsswitch.conf \
    -/etc/ntp.conf \
    -/etc/printcap \
    -/etc/profile \
    -/etc/rc.conf \
    -/etc/resolv.conf \
```

```
    -/etc/src.conf \
    -/etc/sysctl.conf \
    -/etc/ttys \
    -/etc/mail/aliases \
    -/etc/mail/aliases.db \
    -/etc/mail/hal9000.mc \
    -/etc/mail/service.switch \
    -/etc/ssh/*key* \
    -/etc/ssh/*_config \
    -/etc/X11/xorg.conf \
    -/var/cron/tabs/* \
    -/root/.profile \
    -/boot/*.bmp \
    -/boot/loader.conf \
    -/boot/device.hints -; do
    cp --p ${f} ${DESTDIR}${f}
  done
}

#
# Everything else you want to tune in the new system.
# NOTE: Do not install too many binaries here. With the old system running and
# the new binaries and headers installed you are likely to run into bootstrap
# problems. Ports should be compiled after you have booted in the new system.
#
all_remaining_customization () {
  # Without the compat symlink the linux_base files end up on the root fs:
  cd ${DESTDIR}
  mkdir --m 755 usr/compat; chown root:wheel usr/compat; ln --s usr/compat
  mkdir --m 755 usr/compat/linux;      chown root:wheel usr/compat/linux
  mkdir --m 555 usr/compat/linux/proc; chown root:wheel usr/compat/linux/proc
  mkdir --m 755 boot/grub;             chown root:wheel boot/grub
  mkdir --m 755 linux 2k;              chown root:wheel linux 2k
  mkdir --m 755 src;                   chown root:wheel src
  mkdir --m 755 share;                 chown root:wheel share
  mkdir --m 755 dvd cdrom flash;       chown root:wheel dvd cdrom flash
  mkdir --m 755 home;                  chown root:wheel home
  mkdir --m 755 usr/ports;             chown root:wheel usr/ports

  # Create the ntp and slip log files.
  touch ${DESTDIR}/var/log/ntp ${DESTDIR}/var/log/slip.log

  # Make -/usr/src point to the right directory. Optional.
  # Note: some ports need part of the src tree, e.g. emulators/kqemu,
  # sysutils/lsof, sysutils/fusefs, -...
  cd ${DESTDIR}/usr
  if test -"${SRC}" -!= -/usr/src; then
    rmdir src; ln --s ${SRC}
  fi
  if test -"${MAKEOBJDIRPREFIX}" -!= -/usr/obj; then
    rmdir obj; ln --s ${MAKEOBJDIRPREFIX}
  fi
```

```
  # My personal preference is to symlink tmp --> var/tmp. Optional.
  cd ${DESTDIR}; rmdir tmp; ln --s var/tmp

  # Make spooldirs for the printers in my -/etc/printcap.
  cd ${DESTDIR}/var/spool/output/lpd; mkdir --p as od ev te lp da
  touch ${DESTDIR}/var/log/lpd-errs

  # If you do not have -/home on a shared partition, you may want to copy it:
  # mkdir --p ${DESTDIR}/home
  # cd -/home; tar cf -- -. -| (cd ${DESTDIR}/home; tar xpvf --)
}

# vim: tabstop=2:expandtab:shiftwidth=2:syntax=sh:
# EOF $RCSfile: stage_1.conf.default,v $
```

######## stage_1.sh.

stage_2.sh. ### ##### ############ ######## ########## # ##### ###### #####.

```
#!/bin/sh
#
# stage_1.sh -- FreeBSD From Scratch, Stage 1: System Installation.
#             Usage: -./stage_1.sh profile
#             will read profile
#             and write -./stage_1.log.profile
#
# Author:      Jens Schweikhardt
# $Id: stage_1.sh,v 1.7 2008-12-11 19:48:21 schweikh Exp $
# $FreeBSD: head/en_US.ISO8859-1/articles/fbsd-from-scratch/stage_1.sh 38826 2012-05-17 -
19:12:14Z hrs $

PATH=/bin:/usr/bin:/sbin:/usr/sbin

# Prerequisites:
#
# a) Successfully completed -"make buildworld" and -"make buildkernel"
# b) Unused partitions (at least one for the root fs, probably more for
#    the new -/usr and -/var, to your liking.)
# c) A customized profile file.

if test $# --ne 1; then
  echo -"usage: stage_1.sh profile" 1>&2
  exit 1
fi

# ---------------------------------------------------------------------------- #
# Step 1: Create an empty directory tree below $DESTDIR.
# ---------------------------------------------------------------------------- #
```

```
step_one () {
  create_file_systems
  # Now create all the other directories. Mandatory.
  cd ${SRC}/etc; make distrib-dirs DESTDIR=${DESTDIR} TARGET=${TARGET}
}

# ---------------------------------------------------------------------------- #
# Step 2: Fill the empty -/etc directory tree and put a few files in -/.
# ---------------------------------------------------------------------------- #

step_two () {
  copy_files

  # Delete mergemaster's temproot, if any.
  TEMPROOT=/var/tmp/temproot.stage1
  if test --d ${TEMPROOT}; then
    chflags --R 0 ${TEMPROOT}
    rm --rf ${TEMPROOT}
  fi
  export MAKEDEVPATH="/bin:/sbin:/usr/bin"
  mergemaster --i --m ${SRC}/etc --t ${TEMPROOT} --D ${DESTDIR}
  cap_mkdb ${DESTDIR}/etc/login.conf
  pwd_mkdb --d ${DESTDIR}/etc --p ${DESTDIR}/etc/master.passwd

  # Mergemaster does not create empty files, e.g. in -/var/log. Do so now,
  # but do not clobber files that may have been copied with copy_files.
  cd ${TEMPROOT}
  find -. --type f -| sed -'s,^\./,,' -|
  while read f; do
    if test --r ${DESTDIR}/${f}; then
      echo -"${DESTDIR}/${f} already exists; not copied"
    else
      echo -"Creating empty ${DESTDIR}/${f}"
      cp --p ${f} ${DESTDIR}/${f}
    fi
  done
  chflags --R 0 ${TEMPROOT}
  rm --rf ${TEMPROOT}
}

# ---------------------------------------------------------------------------- #
# Step 3: Install world.
# ---------------------------------------------------------------------------- #

step_three () {
  cd ${SRC}
  make installworld DESTDIR=${DESTDIR} TARGET=${TARGET}
}

# ---------------------------------------------------------------------------- #
# Step 4: Install kernel and modules.
# ---------------------------------------------------------------------------- #
```

```
step_four () {
  cd ${SRC}
  # The loader.conf and device.hints are required by the installkernel target.
  # If you have not copied them in Step 2, cp them as shown in the next 2 lines.
  #   cp sys/boot/forth/loader.conf ${DESTDIR}/boot/defaults
  #   cp sys/${TARGET}/conf/GENERIC.hints ${DESTDIR}/boot/device.hints
  make installkernel DESTDIR=${DESTDIR} KERNCONF=${KERNCONF} TARGET=${TARGET}
}

# ---------------------------------------------------------------------- #
# Step 5: Install -/etc/fstab and time zone info.
# ---------------------------------------------------------------------- #

step_five () {
  create_etc_fstab

  # Setup time zone info; pretty much mandatory.
  cp ${DESTDIR}/usr/share/zoneinfo/${TIMEZONE} ${DESTDIR}/etc/localtime
  if test --r -/etc/wall_cmos_clock; then
    cp --p -/etc/wall_cmos_clock ${DESTDIR}/etc/wall_cmos_clock
  fi
}

# ---------------------------------------------------------------------- #
# Step 6: All remaining customization.
# ---------------------------------------------------------------------- #

step_six () {
  all_remaining_customization
}

do_steps () {
  echo -"PROFILE=${PROFILE}"
  echo -"TARGET=${TARGET}"
  echo -"DESTDIR=${DESTDIR}"
  echo -"SRC=${SRC}"
  echo -"KERNCONF=${KERNCONF}"
  echo -"TIMEZONE=${TIMEZONE}"
  echo -"TYPE=${TYPE}"
  echo -"REVISION=${REVISION}"
  echo -"BRANCH=${BRANCH}"
  echo -"RELDATE=${RELDATE}"
  step_one
  step_two
  step_three
  step_four
  step_five
  step_six
}

# ---------------------------------------------------------------------- #
# The ball starts rolling here.
# ---------------------------------------------------------------------- #
```

```
PROFILE="$1"
set --x --e --u # Stop for any error or use of an undefined variable.
. ${PROFILE}

# Determine a few variables from the sources that were used to make the
# world. The variables can be used to modify actions, e.g. depending on
# the system's version. The __FreeBSD_version numbers
# for RELDATE are documented in the Porter's Handbook,
# doc/en_US.ISO8859-1/books/porters-handbook/freebsd-versions.html.
# Scheme is:  <major><two digit minor><0 if release branch, otherwise 1>xx
# The result will be something like
#
#   TYPE="FreeBSD"
#   REVISION="8.0"
#   BRANCH="RC"      { -"CURRENT", -"STABLE", -"RELEASE" -}
#   RELDATE="800028"
#
eval $(awk -'/^(TYPE|REVISION|BRANCH)=/' ${SRC}/sys/conf/newvers.sh)
RELDATE=$(awk -'/^[ \t]*#[ \t]*define[ \t][ \t]*__FreeBSD_version[ \t]/ {
              print $3
            -}' ${SRC}/sys/sys/param.h)

echo -"=> Logging to stage_1.${PROFILE}.log"
do_steps 2>&1 -| tee -"stage_1.${PROFILE}.log"

# vim: tabstop=2:expandtab:shiftwidth=2:
# EOF $RCSfile: stage_1.sh,v $
```

######## stage_2.sh.

stage_3.mk, ####### #### ### #### # ###, ### ################ ### ##–
####### ############.

```
# This file: stage_1.conf.default, sourced by stage_1.sh.
#
# $Id: stage_1.conf.default,v 1.5 2011-05-14 20:44:31 hrs Exp $
# $FreeBSD: head/en_US.ISO8859-1/articles/fbsd-from-scratch/stage_1.conf.default 38826 -
2012-05-17 19:12:14Z hrs $

# Root mount point where you create the new system. Because it is only
# used as a mount point, no space will be used on that file system as all
# files are of course written to the mounted file system(s).
DESTDIR="/newroot"

# Where your src tree is.
SRC="/usr/src"

# Where your obj is.
MAKEOBJDIRPREFIX="/usr/obj"
```

```
# Your kernel config name as from make buildkernel KERNCONF=...
KERNCONF="HAL9000"

# Your target architecture as used for make buildworld TARGET=...
# If you did not specify a TARGET when building world, it defaulted
# to the build architecture (run -"uname --m" to find out if you are unsure).
TARGET="i386"  # amd64 arm i386 ia64 mips pc98 powerpc sparc64

# Available time zones are those under -/usr/share/zoneinfo.
TIMEZONE="Europe/Berlin"



#
# The create_file_systems function must create the mountpoints under
# DESTDIR, create the file systems, and then mount them under DESTDIR.
#
create_file_systems () {
  # The new root file system. Mandatory.
  # Change DEVICE names.
  DEVICE=/dev/daXYZs1a
  mkdir --m 755 --p ${DESTDIR}
  chown root:wheel ${DESTDIR}
  newfs --U ${DEVICE}
  mount --o noatime ${DEVICE} ${DESTDIR}

  # Additional file systems and initial mount points. Optional.
  DEVICE=/dev/daXYZs1e
  mkdir --m 755 --p ${DESTDIR}/var
  chown root:wheel ${DESTDIR}/var
  newfs --U ${DEVICE}
  mount --o noatime ${DEVICE} ${DESTDIR}/var

  DEVICE=/dev/daXYZs1e
  mkdir --m 755 --p ${DESTDIR}/usr
  chown root:wheel ${DESTDIR}/usr
  newfs --U ${DEVICE}
  mount --o noatime ${DEVICE} ${DESTDIR}/usr
}

#
# The create_etc_fstab function must create an fstab matching the
# file systems created in create_file_systems.
#
create_etc_fstab () {
  cat <<EOF >${DESTDIR}/etc/fstab
# Device        Mountpoint         FStype    Options            Dump Pass#
/dev/da0s1b     none               swap      sw                 0    0
/dev/da1s1b     none               swap      sw                 0    0
/dev/da2s2b     none               swap      sw                 0    0
/dev/da3s2b     none               swap      sw                 0    0
/dev/da0s1a     -/                 ufs       rw,noatime         1    1
/dev/da0s1e     -/var              ufs       rw,noatime         1    1
```

```
/dev/da2s1e      -/usr              ufs       rw,noatime          1    1
/dev/vinum/Share -/share            ufs       rw,noatime          0    2
/dev/vinum/home  -/home             ufs       rw,noatime          0    2
/dev/vinum/ncvs  -/home/ncvs        ufs       rw,noatime          0    2
/dev/vinum/ports -/usr/ports        ufs       rw,noatime          0    2
/dev/ad1s1a      -/flash            ufs       rw,noatime          0    0
/dev/ad0s1       -/2k               ntfs      ro,noauto           0    0
/dev/ad0s6       -/linux            ext2fs    ro,noauto           0    0
#
/dev/cd0         -/cdrom            cd9660    ro,noauto           0    0
/dev/cd1         -/dvd              cd9660    ro,noauto           0    0
proc             -/proc             procfs    rw                  0    0
linproc          -/compat/linux/proc  linprocfs rw                0    0
EOF
  chmod 644 ${DESTDIR}/etc/fstab
  chown root:wheel ${DESTDIR}/etc/fstab
}

#
# The copy_files function is used to copy files before mergemaster is run.
#
copy_files () {
  # Add or remove from this list at your discretion. Mostly mandatory.
  for f in \
    -/.profile \
    -/etc/devd.conf \
    -/etc/devd.rules \
    -/etc/exports \
    -/etc/group \
    -/etc/hosts \
    -/etc/inetd.conf \
    -/etc/ipfw.conf \
    -/etc/make.conf \
    -/etc/master.passwd \
    -/etc/nsswitch.conf \
    -/etc/ntp.conf \
    -/etc/printcap \
    -/etc/profile \
    -/etc/rc.conf \
    -/etc/resolv.conf \
    -/etc/src.conf \
    -/etc/sysctl.conf \
    -/etc/ttys \
    -/etc/mail/aliases \
    -/etc/mail/aliases.db \
    -/etc/mail/hal9000.mc \
    -/etc/mail/service.switch \
    -/etc/ssh/*key* \
    -/etc/ssh/*_config \
    -/etc/X11/xorg.conf \
    -/var/cron/tabs/* \
    -/root/.profile \
    -/boot/*.bmp \
```

```
    -/boot/loader.conf \
    -/boot/device.hints -; do
    cp --p ${f} ${DESTDIR}${f}
  done
}

#
# Everything else you want to tune in the new system.
# NOTE: Do not install too many binaries here. With the old system running and
# the new binaries and headers installed you are likely to run into bootstrap
# problems. Ports should be compiled after you have booted in the new system.
#
all_remaining_customization () {
  # Without the compat symlink the linux_base files end up on the root fs:
  cd ${DESTDIR}
  mkdir --m 755 usr/compat; chown root:wheel usr/compat; ln --s usr/compat
  mkdir --m 755 usr/compat/linux;      chown root:wheel usr/compat/linux
  mkdir --m 555 usr/compat/linux/proc; chown root:wheel usr/compat/linux/proc
  mkdir --m 755 boot/grub;             chown root:wheel boot/grub
  mkdir --m 755 linux 2k;              chown root:wheel linux 2k
  mkdir --m 755 src;                   chown root:wheel src
  mkdir --m 755 share;                 chown root:wheel share
  mkdir --m 755 dvd cdrom flash;       chown root:wheel dvd cdrom flash
  mkdir --m 755 home;                  chown root:wheel home
  mkdir --m 755 usr/ports;             chown root:wheel usr/ports

  # Create the ntp and slip log files.
  touch ${DESTDIR}/var/log/ntp ${DESTDIR}/var/log/slip.log

  # Make -/usr/src point to the right directory. Optional.
  # Note: some ports need part of the src tree, e.g. emulators/kqemu,
  # sysutils/lsof, sysutils/fusefs, -...
  cd ${DESTDIR}/usr
  if test -"${SRC}" -!= -/usr/src; then
    rmdir src; ln --s ${SRC}
  fi
  if test -"${MAKEOBJDIRPREFIX}" -!= -/usr/obj; then
    rmdir obj; ln --s ${MAKEOBJDIRPREFIX}
  fi

  # My personal preference is to symlink tmp --> var/tmp. Optional.
  cd ${DESTDIR}; rmdir tmp; ln --s var/tmp

  # Make spooldirs for the printers in my -/etc/printcap.
  cd ${DESTDIR}/var/spool/output/lpd; mkdir --p as od ev te lp da
  touch ${DESTDIR}/var/log/lpd-errs

  # If you do not have -/home on a shared partition, you may want to copy it:
  # mkdir --p ${DESTDIR}/home
  # cd -/home; tar cf -- -. -| (cd ${DESTDIR}/home; tar xpvf --)
}

# vim: tabstop=2:expandtab:shiftwidth=2:syntax=sh:
```

####### ## #####

```
# EOF $RCSfile: stage_1.conf.default,v $
```

######## stage_3.mk.